



A NORTH WEST RUBBER COMPANY



SUREHOOF

EQUINE PAVERS

SPECIFICATIONS:

Thickness: 7/8" or 1-3/4" (23 mm or 43 mm)


Length: 7 7/8 (20 cm)

Width: 6 5/16" (16 cm)

Weight: 1.37 lbs or 2.54 lbs
(0.62 kg or 1.15 kg)

- ✓ **DURABILITY**
SureHoof 100% premium, recycled rubber interlocking pavers are engineered to provide exceptional performance and longevity in demanding outdoor areas that receive high-traffic from horses, people, vehicles and a machinery
- ✓ **SLIP RESISTANT**
Provides a safe, non-slip surface in both wet and dry conditions to reduce the risk of falls and injuries for both horses and people.
- ✓ **COMFORT**
Offers excellent shock absorption and stability which reduces fatigue and joint strain, promoting better overall health and well-being.
- ✓ **NOISE REDUCTION**
The cushioning and sound dampening effect of rubber pavers helps to reduce noise levels in the barn, creating a quieter and less stressful environment for horses.
- ✓ **SAFE & NON-TOXIC**
Sustainable and environmentally friendly recycled rubber composition is animal-safe and non-toxic.
- ✓ **VERSATILE**
Attractive, cobblestone appearance enhances any indoor or outdoor space and is ideal for use in barn aisle ways, wash stalls, feed rooms, tack-up areas, racetrack facilities, walking paths, driveways and terraces.
- ✓ **EASY INSTALLATION**
Fast and easy interlocking installation and virtually maintenance-free. Can be adhered or loose-laid depending on the substrate preparation.

colors available



Founded in 1983

Animat specializes in manufacturing recycled rubber matting and mattress solutions for livestock comfort.

Over 168 Million Square Feet

Animat has installed more than 168 million square feet of animal welfare improvement rubber matting products across more than 25,000 commercial agriculture facilities since 1983.