



A NORTH WEST RUBBER COMPANY



VITELLA

DIN CLASS II CALF MAT

SPECIFICATIONS:

Thickness: 19 mm (3/4")

Maximum Length: 1.83 m (72")

Maximum Width: 1.22 m (48")

Weight: 16.16 kg/m² (3.31 lbs/ft².)

- ✓ **DURABILITY**
Heavy-duty, vulcanized rubber construction engineered and tested to meet the dryness and comfort requirements of DIN 3763 class II for young calves up to 350kg.
- ✓ **COMFORT**
Unique studded underside provides enhanced cushioning to support calf growth and enhance weight gain while reducing noise and stress for the animal.
- ✓ **SLIP RESISTANCE**
Domed surface texture helps minimize the risk of slips and falls, reducing the number of injuries and animal losses.
- ✓ **INSULATION**
Dense rubber construction minimizes heat loss which is especially important for young calves that are more susceptible to temperature fluctuations.
- ✓ **HYGIENIC**
Precision, waterjet cut slats provide faster drainage for cleaner and drier calves.
- ✓ **VERSATILE**
Available in straight-edge or interlocking formats for use in a variety of calf housing areas including individual pens, group housing, and transition spaces. Ideal for both new construction and retrofit.
- ✓ **EASY INSTALLATION**
Easy-to-handle up to 1.22 m x 1.83 m mats secured with Animat's exclusive Slat Lock anchoring system for fast and easy installation.



Animat's Exclusive Slat Lock



Founded in 1983

Animat specializes in manufacturing recycled rubber matting and mattress solutions for livestock comfort.

Over 15 Million Square Meters

Animat has installed more than 15 million square meters of animal welfare improvement rubber matting products across more than 25,000 commercial agriculture facilities since 1983.