



A NORTH WEST RUBBER COMPANY



MAXGRIP

SPECIFICATIONS:

Thickness: 13/16" (20.5 mm)
Max Length: 72" (1.83 m)
Max Width: 48" (1.22 m)
Weight: 4.6 lbs/ft². (20.6 kg/m²)

- ✓ **DURABLE**
Engineered with premium, 13/16" thick vulcanized rubber with a 36% improvement in abrasion resistance for maximum durability.
- ✓ **HIGH-GRIP SURFACE**
MaxGrip's raised diamond surface is specifically designed to increase traction and prevent injuries due to slipping allowing cows to walk more confidently and safely.
- ✓ **COMFORT**
Reduces hoof injuries and lameness for increased mobility, improved rate of gain and feed efficiency.
- ✓ **EASY INSTALLATION**
Fast and easy installation requires only a drill when using Animat's exclusive Slat Lock anchoring system.
- ✓ **VERSATILE**
Available in slatted or non-slatted options with or without interlocking. All custom cut to your size requirements.
- ✓ **LONG LASTING**
Backed by a 7 Year warranty.



Animat's Exclusive
Slat Lock



Founded in 1983

Animat specializes in manufacturing recycled rubber matting and mattress solutions for livestock comfort.

Over 168 Million Square Feet

Animat has installed more than 168 million square feet of animal welfare improvement rubber matting products across more than 25,000 commercial agriculture facilities since 1983.